

LILY

Self-Leveling Borehole Tiltmeter

The LILY Self-Leveling Borehole Tiltmeter is designed for volcanic and tectonic research and for monitoring of hydraulic fracturing and other subsurface processes in the oil and gas industry. LILY is the culmination of over 25 years of experience in the fields of instrumentation and geophysics by the engineers and scientists at Applied Geomechanics. Its small diameter and high-pressure stainless steel housing give it ruggedness and versatility for demanding field projects.

The dual-axis tiltmeter senses angular movement in two orthogonal vertical planes using precision electrolytic tilt sensors. The digital electronics convert the tilt signals to an easily recorded RS485 (RS422) data stream consisting of tilt, azimuth, temperature, serial number and clock time. Data output in NMEA 0183 format is a standard feature.

The LILY tilt sensors can self-level on command through a range of ± 10 degrees and have < 5 nanoradians resolution over a dynamic range of ± 330 microradians. LILY incorporates an innovative new design* that achieves high mechanical stability, necessary for stable long-term measurements, at a much lower cost than was previously possible in instruments of this type.



Contact us today for more information about this exciting new instrument or to place an order!

Specifications	
CHANNELS	X tilt, Y tilt, azimuth, temperature
RESOLUTION	< 5 nanoradians
REPEATABILITY	Same as resolution under static conditions
MEASUREMENT RANGE	± 330 μ radians
SELF-LEVELING RANGE	± 10 degrees
LINEARITY	0.2% of full span
FREQ. RESPONSE	< 1 Hz
TEMPERATURE COEFS.	Span: $K_s = +0.02\%/^{\circ}\text{C}$, Zero: $K_z = \pm 3$ μ radians/ $^{\circ}\text{C}$, typical. Smaller coefficients available at higher cost.
AZIMUTH DETECTION	On-board magnetic compass, 0° to 360° output
SAMPLE RATES	User-selectable from 10/second to 1/hour
DATA STORAGE	2 Megabytes of nonvolatile Flash memory (64,000 samples)
DATA FORMATS	Formats: NMEA XDR, Trimble proprietary, Ashtech compatible, Simple (x, y, temperature, serial no.)
SERIAL OUTPUT	RS485 (RS422). Baud rate: 9600, 19200 (default), 28800, 57600, 115200, 230400
REAL-TIME CLOCK	Present. Accuracy better than 10 minutes/year.
POWER REQT'S.	7 to 28 VDC @ 30 mA when sampling or transmitting, < 10 mA in sleep mode, sampling 1/minute, 250 mV peak-to-peak ripple max., reverse polarity protected
SURGE PROTECTION	All input and output lines are tranzorb protected.
CONNECTIONS	6-pin high-pressure neoprene connector standard, other connectors available
ENVIRONMENTAL	-25°C to $+85^{\circ}\text{C}$ operational, -30°C to $+100^{\circ}\text{C}$ storage. Pressure rating: 345 bars (5000 psi)
DIMENSION & WEIGHT	51mm (2 inches) diameter x 915mm (36 inches); detachable handle is 150mm (6 inches) long. 4.5 kg (10 lb)
MATERIALS	304 stainless steel, nonmagnetic

Specifications are subject to change without notice as the result of ongoing development.

* Patent pending