

Note: Power input is into the DC power board and utilizing the FlexCharger Solar panel regulator.				
Receiver is attached to a powered antenna splitter				
Equipment type	Enabled features	input voltage	input amps	watt
NetR9 (GPS)	none	15	0.204	3.40
EdgeRouterX				
Bullet M2HP Titanium				
RV50	NO SIM	15	0.062	1.10
NetR9 (GPS) + EdgeRouterX	none	15	0.392	6.00
NetR9 (GPS) + EdgeRouterX + bullet	none	15	0.540	8.20
NetR9 (GPS) + bullet	none	15	0.400	6.10
NetR9 (GPS)	streaming RT to computer	15	0.205	3.10
NetR9 (GPS) + EdgeRouterX	streaming RT to computer	15	0.312	5.00
NetR9 (GPS) + bullet+ RV50	NO SIM	15	0.500	7.50
NetR9 (GPS) + RV50	NO SIM	15	0.261	4.30
PolaRx5	GNSS	15	0.234	3.50
NetR9	GNSS, RTX	15	0.372	5.50
NetR9 (GPS)	slow charging internal battery	13	0.204	8.60
NetR9	GNSS	15	0.372	4.50
NetR9	GPS, GLS	15	0.270	3.70
NetR9	, RTX	15	0.301	4.10
NetR9	, GAL, RTX	15	0.301	4.50
NetR9	GPS,GNSS, RTX	15	0.301	4.80
NetR9 (GNSS)	slow charging internal battery	13	0.204	9.50
Note: if utilizing UPS feature, set charging voltage to +15 volts				