

# Trimble NetRS receiver firmware version 1.2-0

Article Number: 364 | Rating: Unrated | Last Updated: Tue, May 4, 2010 at 9:51 PM

Trimble NetRS firmware version 1.2-0 is available for download here. [Version 1.3-0 has been released](#) and all eligible users are advised to upgrade.

Download links for the installation file and official release notes are below.

[NetRS-1.2-0.ppc.rpm](#)

[Trimble\\_NetRS\\_Ver120\\_RelNotes.pdf](#)

Details from the release:

Firmware Version 1.2-0

Firmware Date 2007/04/26

To install this release use the NetRS Browser interface to upload this file onto your NetRS. Then click the Install button. The installation process will take several minutes.

Expected Installation Time : 400 seconds

=====  
Trimble NetRS Firmware Version 1.2-0  
=====

This is a Major release containing numerous feature enhancements and bug fixes.

-----  
New Features  
-----

- GPS tracking software updated to allow simultaneously tracking of L2Y and L2C signals. Configurable via the Web-GUI interface using:  
Receiver Configuration -> L2 Tracking
- Support added for Trimcomm command 0x53-CHANCTRL, to allow GG-Base to control L2 Tracking Modes.
- Added ability to log Raw WAAS/SBAS data to T00 files.
- In RT17 streams, Record 17's can now be replaced with Record 27's. This allows collecting data with simultaneous L2Y+L2C tracking. Configurable via the Web-GUI interface.
- In T00 data logging, added the ability to replace Record 17's with compressed Record 27's. This allows collecting data with simultaneous L2Y+L2C tracking. Configurable via the Web-GUI interface.
- Trimcomm support for command 0x49-COMMOUT enhanced to allow selection of Record 27's in an RT17 output stream.
- Various Met/Tilt interface enhancements.  
Met/Tilt interface enhanced to allow faster rates of 1, 5, 15 and 30 seconds. In addition, a control was added to Binex data logging and streaming to allow selective inclusion of Met/Tilt results. If all records are disabled except Met/Tilt, it is possible to log or stream only the Met/Tilt results.
- RT17 enhancements involving GPS Ephemeris Data.
  - o Ephemeris issues will not be streamed if they are more than 24 hours old.
  - o Ephemeris data will be re-transmitted every five minutes for tracked satellites and every 15 minutes for other satellites.
  - o Ephemeris data for new ephemeris issues will be transmitted as soon as possible after first being received.
  - o A complete set of ephemeris data will be transmitted whenever a new client connection is made to a TCP or UDP port.

- RT17 streams now include periodic Record-19 week/time sync records. These records are now sent whenever a new client connects and every five minutes, to provide unambiguous time stamps.
- RTCM Version 3.0 output capability added to I/O streams.
- Added support for a few new antenna types.
- Trimcomm command SetIdle (0x4f) can now be used to control clock steering mode.
- Trimcomm command GetIdle (0x3d) has been added to allow querying of Elevation Mask, PDOP Mask, and Epoch Interval. All other fields in the response are sent as zeroes.
- Trimcomm command 0x71 added has been added to allow querying and setting the Reference Frequency Source and presence.
- More obvious information has been added to console output and to messages files regarding system shutdowns due to the power-saving mode.

---

#### Bug Fixes

---

- RT17 streams started by Trimcomm commands no longer lose epochs or show loss-of-lock when the same start command is issued.
- The system had difficulty switching between L2Y and L2C tracking. These have been fixed.
- Unhealthy satellites are now prevented from being used in position fixes when the Ignore Health mode is used.
- SSL logs occasionally become huge over time. SSL log files (from https access mode) are now pruned properly at regular intervals.
- Binex L2 Phase values will be marked invalid whenever L1Phase is marked invalid.
- Binex measurement cycle slip indications are now more reliable. This should prevent any persistent out-of-range phase indications.
- "FATAL" console errors on Shutdown have been subdued. These were actually unimportant warnings.
- The Ephemerides Data Service now includes data for ALL satellites (not just those being tracked) and the ionospheric data.
- T00 files formerly did not contain ephemerides for unhealthy SVs. Now they do.
- Once-only Met/Tilt commands were not being issued at logged file rollovers. Now they are.
- System logs occasionally showed the ntpd error: "Interrupted system call". These were unimportant warnings and now should be gone.
- Using https protocol with some versions of Internet Explorer caused lots of messages to the error\_log. These should now be gone.
- Fixed numerous bugs associated with PRN 32.
  - o PRN32 ephemeris data not completely erasing with "Clear GPS Data".
  - o PRN32 data observables not getting into Binex data streams & files.
  - o PRN32 ephemeris data would not be sent via the query services.
  - o PRN32 data wouldn't have been smoothed or filtered properly.
- Antenna information in T00 files was not properly encoding the height reference point method.
- L1-C/No values weren't updating at a 10Hz rate in files or streams.

Now they do.

- Met/Tilt data stopped forwarding to a Binex stream if the Binex stream was restarted. Now the data keeps streaming.
- Fixed three things associated with Trimcomm command SetSesStn (0x42)
  - o It was interpreting Latitude and Longitude values as Radians instead of Degrees. Now matches the documentation and other receiver types.
  - o It had problems dealing with the 50 character description string, if the string was not NUL-0x00 terminated. The command properly handles the case where the full 50 characters are specified without a NUL
  - o It was corrupting the BinexId string. It no longer does that.

Posted by: **Freddy Blume** - Tue, May 4, 2010 at 9:51 PM. This article has been viewed 12686 times.

Online URL: <https://kb.unavco.org/kb/article/trimble-netrs-receiver-firmware-version-1-2-0-364.html>