

GPS Surveying with 1mm Precision Using Corrections for Atmospheric Slant Path Delay (1997)

181 Beth Bartel October 17, 2008 [Atmospheric Effects and Measurements](#) 1432

Alber, C., R. Ware, C. Rocken, and F. Solheim (1997), GPS Surveying with 1 mm Precision Using Corrections for Atmospheric Slant Path Delay, Geophys. Res. Lett., 24(15), 1859-1862.

GPS surveying with 1 mm precision using corrections for atmospheric slant path delay

Chris Alber, Randolph Ware, Christian Rocken, Fredrick Solheim
University Navstar Consortium/University Corporation for Atmospheric Research

Abstract. Multipath and atmospheric effects can limit GPS surveying precision. We surveyed a 43 km baseline using large diameter choke ring antennas to reduce multipath and pointed radiometer and barometric data to correct for atmospheric slant delay. Based on 11 daily solutions, atmospheric slant delay corrections improved vertical precision to 1.2 mm rms and horizontal precision to sub-mm. Applications for high precision GPS surveying include deformation monitoring associated with earthquake and volcanic processes, subsidence, isostasy, and sea level measurements; monitoring of atmospheric water vapor for climate and global change research, and to improve the resolution of synthetic aperture radar; calibration of satellite altimeters; and precise satellite orbit determination.

[See [attached .pdf file](#) for more.]

Online URL:

<https://kb.unavco.org/article/gps-surveying-with-1mm-precision-using-corrections-for-atmospheric-slant-path-delay-1997-181.html>