## Stainless Steel Pin with Mast Overview

324 Beth Bartel March 14, 2018 Antenna Masts and Monument Pins 1747

## Stainless Steel Pin with Mast

Back to comparison table	<b>Mount Commonly Used</b>	Stabi lity	Cost	Install Time	Labor	Substrate
	Cup with brass adapter	med- high	\$265-3 50	1 hr		BR, R

Stainless steel mast designs may vary. In general, they consist of a threaded pin set into bedrock with cement or epoxy, with a threaded mast screwed onto the pin. Throughout the semi-permanent GNSS network in Afar, Ethiopia (E. Calais, Purdue University), pins are ten inches long and masts are 1"-diameter and 0.5m (19.7") long (shown below). The pin is installed as close to vertical as possible; a stainless steel cup with a threaded brass adapter is used for the antenna mount. The cup does not allow for precise leveling but does allow for the antenna to be oriented to north. A dimple on the pin allows the pin to be used as a survey marker should the mast be removed.



# Pros

- Inexpensive (e.g. ~\$110-200 for the pin and mast, \$150 for the mount)
- Can be installed with a battery-powered drill
- Small footprint, low-profile
- Short installation time (<1 hr)
- Can be installed on a rooftop or other stone or cement structure
- more stable than the all-thread mast


### Cons

• Can only be installed in solid material

# Design and Construction

A battery-powered drill is all that is needed for installation of the pin.

#### **Documents**



Threaded monument pin (Conquest pin) machining instructions (cost \$100)

Please note: Alternatively, a 8" long SS 5/8" all-tread rod with a SS nut epoxied or welded on to the rod can be substituted for the pin mentioned above.

Similar to the all tread mast but installed flush to the ground. See the <u>article</u> on the all tread rod mast.

**Installation Photos** 



Feleke Worku of the Ethiopian Mapping Agency uses a battery-powered Hilti hammer drill to drill the hole for a monument pin in the Afar network.

# **Approximate Cost**

\$165-250

This cost is for the monumentation only; the antenna mount is not included.

# Materials

• pin

- mast
- epoxy or quick-setting, expansive concrete
- Loctite or other glue for threads (optional)

#### **Tools**

- battery-powered drill
- tube to blow rock flour out of the hole
- level
- adjustable wrenches, vice grips, or pipe wrenches for tightening threads (recommended)
- compass

## Mount Commonly Used



A 5/8" threaded leveling mount (cost \$150) can be used, but we commonly use a simple non-leveling mount consisting of a stainless steel cup holding a brass adapter. The antenna is screwed onto the brass adapter and can be rotated to north. The adapter is then held in place in the cup with a set screw. The monument itself is installed as close to vertical as possible.

*unavco.org*)

Send questions or comments about this page to Support (support