

UNAVCO Resources: Radomes

520 Beth Bartel May 26, 2023 [GNSS Radomes](#) 5767

UNAVCO Resources: Radomes

Many permanent GNSS stations are equipped with antenna radomes as a means of protection against general wear, to prevent the buildup of debris and snow, and to discourage people and animals from disturbing the antenna. Antenna radomes affect the signal propagation thereby altering the antenna's absolute phase center. Users should apply the appropriate absolute phase center model for each antenna and radome combination processed for precise coordinate determination. Most antenna/dome corrections are typically provided to the GNSS community by the IGS in the [ANTEX format](#).

The two currently most commonly used radomes are the short and tall SCIGN domes, shown below.



Radome Testing at UNAVCO (Historical)

- [Assessing the Impact of the SCIGN Radome on Geodetic Parameter Estimates \(2007\)](#)
- [UNAVCO Testing of the SCIGN Radome \(2001\)](#)
- [The Effect of Antenna Covers on GPS Baseline Solutions \(1997\)](#)

Ordering information:

SCEC/University of Southern California
3651 Trousdale Parkway, Suite 169
Los Angeles, CA 90089-0742
scec-at-usc.edu

Tel: (213) 740-5843

Fax: (213) 740-0011

Online URL: <https://kb.unavco.org/article/unavco-resources-radomes-520.html>